



# P-Series Detection Cameras

## Powerful yet affordable

### Benefits of the P-Series



Robust detection – Vehicle and bicycle differentiation with data collection



All-weather operation – Optimized for outdoor conditions; available heater for ice prevention



Easy to install – simple connections on back of camera



### Versatility with value

The P-Series Detection cameras from Iteris are integrated machine vision processors and cameras, designed to use on all types of intersections outside of North America.

The P-Series system provides a versatile, high resolution video traffic camera specially optimized for machine vision processor technology. Each P-Series camera includes a high sensitivity color imager to ensure accurate vehicle detection in all lighting conditions, and agencies have the choice of two fixed or variable zoom cameras depending on functionality required.

The P-Series solution includes the interface controller that resides in the roadside cabinet. All user interface functions are performed through the interface controller such as virtual zone placement, detector output assignment, and video monitoring.

### Affordable and accurate

As video cameras are mounted above-ground, installation is far less labor intensive and requires minimal traffic encroachment, thereby reducing lane closures and enhancing safety for installers.

The Iteris P-Series detection system is a complete video vehicle detection solution that is a cost effective replacement to inductive loops and other sensor technologies for many smaller intersections. Other applications include advance detection, highway, ramp metering, and construction-work zones.

# P-Series Detection Cameras

Powerful yet affordable

## More benefits

- Affordable installation - low cost, easily attainable CAT5e or CAT6 cable
- Central viewing - by pairing with an EdgeConnect (or any video server), can enable remote video viewing
- Adaptive Control ready - detection system available for any adaptive control product

## SPECIFICATIONS

	P-Series Cameras	Interface Controller	
<b>Features</b>	Color imager 768 x 494 effective pixels 530 TV Lines Automatic white balance >50dB S/N ratio .0 to 10,000 lux	DIN rail mount Compact design Easy terminations 16 fail safe open-collector Outputs (30 VDC @ 50 ma max.)	
<b>Lens</b>	<b>P50</b> Fixed focal length 54° FOV adjustable focus	<b>P80</b> Fixed focal length 85° FOV adjustable focus	<b>PI00</b> Variable focal length 4.6 to 65° FOV adjustable focus
<b>Connections</b>	Pluggable terminal-6 way • 2 x DC Power • 2 x Differential video • 2 x Differential control		
<b>Dimensions</b>	13.5" (L) x 4" (D) 34.3cm x 10.2cm Without bracket	3" x 6" x 2.5" 7.6cm x 15.2cm x 6.4cm	
<b>Weight</b>	4.25lb (1.92kg)	0.5lb (0.2 kg)	
<b>Op. Temperature</b>	-31°F to +165°F (-35°C to +74°C)	-31°F to +165°F (-35°C to +74°C)	
<b>Humidity</b>	0 - 100% relative	90% relative, non-condensing	
<b>Vibration</b>	0.5G, 3 axes, 5-30 Hz	0.5G, 3 axes, 5-30Hz	
<b>Shock</b>	10G, all 3 axes	10G, 3 axes	
<b>Power</b>	24 to 48VDC, IIV typical 22W max	12 VDC, 0.3 amps 3.6 watts	
<b>Warranty</b>	3 years limited warranty	3 years limited warranty	



Copyright © 2016 Iteris, Inc. All rights reserved.

NOTICE: Iteris, Inc. reserves the right to change product specifications without notice. Information furnished is for informational purposes only. This information may not be complete or the latest revision. For the most up-to-date information, please contact Iteris, Inc.